



Ref.	Dimensions (mm)
Flange	F03
C x depth	M5x8
E	36
B	9
O	10.2
A1	224
G	10
H	20.2
I	9
J	24
K	18
L	80.4
M	32.7
N	47.7
P	34
Q	39
R	10.9
S	20
T	60.4
X	73
W	5
Ancillaries Attachment	AA0

Spring return Actuators Normally Closed (N.C.) - Output Torque related to rotation angle, in Nm (0° valve closed 90° valve open)

Spring Torque				Air pressure supply in bar																																
SIZE	0°	50°	90°	2,4			2,8			3			3,5			4,2			5			5,6			6			7			8					
				0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°						
2,8	5.0	3.7	7.5	5.7	2.6	3.2	7.5	3.7	5.0	8.4	4.2	5.9	10.6	5.6	8.1	13.8	7.4	11.3																		
3,5	6.3	4.7	9.4							7.2	3.3	4.0	9.4	4.7	6.3	12.6	6.5	9.4	16.1	8.7	13.0	18.8	10.3	15.7												
4,2	7.5	5.6	11.3										8.2	3.7	4.4	11.3	5.6	7.5	14.9	7.7	11.1	17.6	9.3	13.8	19.4	10.4	15.6	23.8	13.1	20.0	28.3	15.7	24.5			
5,6	10.0	7.5	15.0																12.3	5.9	7.3	15.0	7.5	10.0	16.8	8.6	11.8	21.3	11.3	16.3	25.7	13.9	20.7			

Technical Data

Max Pressure	** Min Pressure	Rotation	Stroke Adjustment	Screw Stroke Adjustment	*Moving time (sec.)		Operating temperature (°C)
					Opening	Closing	
8.4 bar	2.4 bar	92° -1° +91°	-	-	0.11	0.13	Standard -20°C +80°C

Weight Kg	Chamber Ø (mm)	Air volume L/cycle	Maximum flange torque values	Spring return Actuator with spring force 2.8, is manufactured with only one spring cap and normal end cap.	A2	Weight Kg
1.7	40	0.09	F03 = 32 Nm		179	1.5

*The moving time could vary on different operating and installation factors.

Operating Medium

The operating medium shall have a dew point equal to -20 °C or, to be at least, 10 °C below the ambient temperature (ISO 8573-1, Class 3).
The maximum particle size shall not exceed 40 µm (ISO 8573-1, Class 5).